

# The market-leading Optimax® machinery range now available from **Westbury Packaging**



## TVX High speed friction weld strapping tools

### Features

The TVX Li-ion battery powered tool is one of the fastest on the market - in less than three seconds, the strap is tensioned, sealed and cut.

The ergonomic and rugged design assists maximum operator comfort, with minimal effort. Packages such as boxes, pallets, bales and crates can be safely strapped. Strap feeding is extremely simple, with both straps being inserted together. The TVX has an exceptional tension range and applies up to 240kg (2400N) with ease. The flexible sealing mode allows you to choose from semi-automatic or single button fully automatic operation.

### Specifications

- > Strap type compatibility: Polyester: 0.4mm - 1.05mm Polypropylene: 0.7mm - 1.05mm
- > Strap width: 12/16mm - please specify when ordering
- > Strap tension: Adjustable up to 240kg (2400N) subject to strap specifications



## TMS300 Semi-Auto Strapping Machine

### Features

- > Compatible with 6-16mm polypropylene machine strapping on 200mm and 280mm internal diameter strapping cores
- > Safety interlocked stainless steel top plate
- > Enclosed cabinet
- > Fixed/swivel castors
- > External manual strap tension adjustment

### Benefits

- > Simple and reliable to use
- > Very mobile
- > Sealing mechanism and coil protected from damage and contamination inside fully enclosed cabinet

### Specifications

- > Dimensions (W x D x H): 920 x 595 x 785mm
- > Machine weight: 100kg
- > Max strappable package weight: 120kg
- > Min/max strap tension: 15-45kg (depending on strap)
- > Cycle time: 2.5 seconds @ 50Hz
- > Power supply: 230V 50Hz
- > Power consumption: 0.3kW

Our best-selling Optimax® semi-automatic strapping machine



## AFS900 Automatic Strapping Machine

### Features

- > Auto strap feed
- > Short feed sensor and auto strap re-insertion
- > Electronic tension control
- > Auto loop ejector



Electronic tension control



Loop ejector automatically clears unwanted strap



Auto strap feed requires no access to the inside of the machine

### Benefits

- > One of the most advanced strapping machines in its class
- > Fast tension adjustment
- > Minimal downtime and coil changeover

### Specifications

- > Dimensions (W x D x H): 1630 x 620 x 1740mm
- > Min/max strap tension: 10-70kg
- > Cycle time: 2.6 seconds @ 50Hz
- > Power supply: 230V 50Hz
- > Power consumption: 1.2kW

**WESTBURY**  
PACKAGING 

For more information and **the very best prices** on the complete range of Optimax® packaging machinery, contact our sales team on **01373 826329**

31 Lancaster Road Bowerhill Industrial Estate  
Melksham Wiltshire SN12 6SS

[westbury-pkg.co.uk](http://westbury-pkg.co.uk)  
your packaging partners